

IC 34

PRODUCT FEATURES

- 4 x 3.5" High efficiency neodymium drivers
- 120° x 40° directivity
- Clear and natural sound
- Very light weight (4 kg)
- Ultra-compact unobtrusive design
- Extrusion aluminium housing with black or white powder coating
- 3 x M6 mounting points for SMB bracket and safety wire fixing
- IPX5 protection

SPECIFICATIONS

ACOUSTICAL	
Frequency range (-3 dB)¹	150 Hz - 17 kHz
Frequency range (-6 dB)¹	120 Hz - 16 kHz
Frequency range (-10 dB)¹	100 Hz - 20 kHz
Coverage angles (-6 dB) [H x V]	120° x 40°
Nominal impedance	8 Ω
Sensitivity¹	94 dB
Peak power	800 W
Continuous power²	200 W
Maximum Peak SPL³	129 dB
System type	1-way passive system
Transducers	4 x 3.5" neodymium drivers (1" voice coil)
Enclosure type	Vented box
Connectors	Input / Link: Phoenix contact MSTB 4-pins
User controls	2-positions input selection switch
Wiring	Pins 1+/1- or 2+/2- (switchable)

¹ Whole space, 1W / 1m, on axis. With dedicated IA 402D amplifier's preset

² According to EIA-426B Standard (based on RMS Voltage)

³ Max Peak SPL = Sensitivity + 10log₁₀(Continuous Power) + 12 dB Crest Factor

All product specifications are subject to change without prior notice.



PRODUCT DESCRIPTION

IC 34 is a bassreflex installation column speaker equipped with four state-of-the-art 3.5" neodymium drivers. They were specifically designed to reproduce the full range of frequency band by designing a custom basket with an advanced cooling module and high-end paper membrane.

Slim and subtle in appearance, IC 34 comes in a classy brushed-aluminum housing to blend well into many different environments.

MECHANICAL	
Product dimensions [H x W x D] (Including rigging)	462 x 118 x 155 mm
Net weight	4 kg
Packaging dimensions [H x W x D]	620 x 268 x 375 mm
Total weight	10.1 kg
Cabinet	Die-cast aluminium housing, plastic
Cabinet finishing	Black or white powder coating
Grille	Powder coated perforated steel
Mounting	Center and bottom mounting points for SMB bracket Safety wire fixing point

ACCESSORIES	
Smart Mounting Bracket	SMB

PRODUCT DRAWINGS

